

PROTECTING PEOPLE AND THE ENVIRONMENT. ENSURING STABLE OIL AND GAS PRODUCTION





## TRELLEBORG VIKING HPT

HPT is a fire and blast rated flexible seal. We can offer a range of products for several applications. HPT is made of a rough and durable material designed for offshore environments, connecting modules and maintaining fireproof partitioning. We design and offers a solution that fullfils your requirements.

The HPT system is offered as a pipe penetration seal. This seal closes the pipe penetration and allows movements of the pipe during operation. The seal can be delivered in a varity of sizes, shapes and fire classes. It is easy to install on bulkheads and decks, single and double sided on exposed and on unexposed side. The HPT is also delivered as vessel seal, conductor seal, linear seal, hang-off protection, equipment protection and lifeboat tunnel seal.

## APPLICATION

- Quick and easy installation
- Easy inspection of equipment
- Weather barrier
- Fire and blast barrier
- Jet-fire resistant up to 2 hrs.
- H-fire approved according to IMO A754 (18)
- ▶ Blast up to 1,25 bars
- Resistant to hydrocarbon splash,
  - Ozon and UV-light

- Closes open spaces and gaps
- Tailor made in any shape and sizes
- Wrap around solution
- Individual tagged according to requirements
- Good weather properties
- ▶ Operating temperature range –40 °C to 90°C
- Cost efficient
- Negligible combustion products
- Maintenance free

## MAIN REFERENCES

Amenam: Total Bayu Undan: ConocoPhilips

Kvitebjørn: Statoil Åsgard: Statoil

Hibernia: Petro Canada Ula: BP

Sakhaline: SEIC Ekofisk 2/4M: ConocoPhilips



Trelleborg Viking AS Postal address: Trelleborg Viking AS, P.O Box A, NO-3051 Mjøndalen, Norway Visiting address: Kalosjegata 15, 3055 Krokstadelva, Tel.: +47 32 23 20 00 Fax: +47 32 23 22 00 www.trelleborg.com/viking, e-mail: viking@trelleborg.com

